

TECHNICAL DATA SHEET



Product Name: G3 PASTE

Product Number: G3-250*, G3-400, G3-1000, G3-3000



Product Description

Regular Grade Paste Compound developed specifically for use on all modern original and refinish paint systems: medium solids & high solids (fresh – cured).

Characteristics

Water based
Silicone free
Regular grade paste compound
Use with water

Physical Properties

Specific Gravity: 1.44
Viscosity: ca 52,000 cps
Flash Point: 83°C
pH: 9.41
Solid Content: 165g (G3-250), 264 (G3-400),
660g (G3-1000), 1980 (G3-3000)
VOC Content: 28g (G3-250), 44.8g (G3-400),
112g (G3-1000), 336g (G3-3000)
Colour: Off white
Consistency: Paste

Packaging

250g / 400g / 1kg / 3kg

Shelf Life

Farécla products are guaranteed two (2) years shelf life when unopened and stored in a cool dry place.

Applications

G3 Paste is recommended for removing P1500 of finer abrasive marks quickly and easily.

Storage and Handling

Store at room temperature.
Protect from frost.
Shake container prior to use.

Additional Information

Professional users may refer to the Material Safety Data Sheet for this product available from Farécla Products Limited upon request.

*This pack size is not available in the UK



Directions for Use

1. After wiping the panel with a suitable degreaser, soak the Advanced G Mop Compounding Foam in clean water. Squeeze excess water from foam, fit to a polishing machine and spin off excess water.
2. Apply a small amount of G3 Paste to the paint surface using a cloth and spread uniformly over the surface using the Compounding Foam before starting the machine to reduce splatter.
3. Begin compounding with a free running speed of 1500 – 1800 rpm and the foam initially held at a slight angle (15°). Compound until marks have been removed, and finish with the foam held flat on the surface.

Keep the Advanced G Mop damp by spraying minimal amounts of clean water from a Farécla Water Spray Bottle. Check at regular intervals to see if the flattening marks have been removed and add more G3 Paste if necessary and repeat the procedure until all the marks are removed and a satisfactory gloss is achieved.

4. Finish off by using light pressure and water only and remove any residue with a Farécla Finishing Cloth. Buff the paint surface with the Farécla Finishing Cloth to achieve a smear-free, high gloss finish.

For an enhanced high gloss finish on dark colours, follow with G10 Extra Fine Grade Liquid Compound on an Advanced G Mop Polishing Foam.

Limited Warranty

Farécla Products Limited warrants this product for a period of two (2) years from the date of purchase by the first user. If this Farécla product is proved to be defective, Farécla Products Limited will, at its option, refund the purchase price, or replace the defective product with a like product once the defected product has been returned. This warranty applies only if the product is not altered or damaged or used beyond its intended use. This warranty is in lieu of all other warranties expressed or implied. This warranty specifically excludes incidental or consequential damages.

Manufactured in England by
Farécla Products Limited
Broadmeads
Ware
Hertfordshire
SG12 9HS

Dated January 2005

